



As reassuring as daylight.

GasAlertClip2 & GasAlertClip3
H₂S, CO, O₂ or SO₂ H₂S or CO

- Two or three years of protection
- Zero maintenance costs
- Compact and lightweight
- Event logging
- Simple one-button operation
- Audible, visual and vibrating alarms
- Compression proof test
- Rugged IP 6800* housing

5 year model test 3 year model test

MicroClip
multi gas detector

- Simple one-button operation
- Displays H₂S, CO, O₂ and LEL (combustible gas) concentrations simultaneously
- Ultra-compact, water resistant housing with built in concussion proof boot
- Standard stem logging and event logging
- Durable stainless steel alligator clip
- Ideal for confined space applications
- Dry

*Housing and case not included. All components are sealed internally.

BW Technologies
By Instrument

For further information on the BW Technologies range of products

Contact Us

Toll Free: 1800 607 558

Telephone: +61 8 9244 4566

Facsimile: +61 8 9244 4577

Address: Unit 2/81 Guthrie Street, Osborne Park WA 6017

Email: info@accessunlimited.com.au

Web: www.accessunlimited.com.au



GasAlertMicro 5 IR

CO₂, H₂S, CO, O₂, SO₂, PH₃, NH₃, NO₂,
HCN, Cl₂, ClO₂, O₃, and Combustibles

Five-Gas Detector



Protect Yourself

- △ Smaller and lighter than competitive instruments
- △ Water-resistant design in an integral concussion-proof enclosure
- △ Continuous LCD shows simultaneous gas concentrations for five gases
- △ 0 - 50,000 ppm measurement of CO₂ (Carbon Dioxide)
- △ Integral motorized pump option for remote sampling
- △ Two power options: AA alkaline or rechargeable hot-swappable battery packs
- △ Provides 95 dB alarm tone and two bright wide-angled alarm bars
- △ Equipped with internal vibrating alarm for high noise areas
- △ Multi-language support in English, French, German, Spanish, and Portuguese
- △ Three backlight options: standard—activates in low light (auto), in alarm (auto) and reactivates on-demand; alarm only—activates in alarm conditions and reactivates on-demand; stealth mode
- △ Four alarm levels: instantaneous Low and High Alarm for all gases; TWA (time-weighted average) and STEL (short-term exposure limit) for CO₂ and toxic gases
- △ Simple automatic calibration procedure; compatible with BW MicroDock II automatic test and calibration station
- △ Records TWA, STEL, and maximum exposures to gas and displays readings on command
- △ User selectable field options include: Combustible correction factor, language selection, confidence beep, span level, set TWA/STEL calculation choice, set calibration due date, pass code protection, latching alarm, "SAFE" display function, stealth mode, and selectable ppm resolution for some gases (e.g. SO₂ 0.1 ppm)
- △ Full function self-test of: sensor, battery and circuit integrity; and audible/visual alarms
- △ Compatible with BW's MicroDock II — automated test and calibration station



**Water
Resistant**



GasAlertMicro 5 IR
with integrally attached pump



Optional rechargeable battery
and slip-in cradle charger

Ordering Information

GasAlertMicro 5 IR is delivered ready for use with sensors (as specified), sensor compartment cover for diffusion operation, battery (as specified), stainless steel alligator clip, calibration cap/hose, 2 extra electrode stacks, instructions in local languages and interactive training CD.

Battery/Charger Options

Consult factory for battery/charger options
Rechargeable battery pack and desktop/wall mountable slip-in cradle charger

User-Downloadable Datalogger Option

Datalogging versions include 32 MB MMC card, software and an IR port for use with the MicroDock II automated calibration and test station.

Pump Option

Includes detector, standard accessories plus integrally attached motorized pump and cover (installed), 12 in./30 cm sample probe with hydrophobic barrier (water trap) and particulate filters, 5 ft./1.5 m sampling tubing, five spare particulate filters, and one spare water trap filter.

Value Added Confined Space Kits

Kits include detector, standard accessories plus a hard-sided, foam-lined carrying case, 10 ft./3 m sampling hose, sample probe, battery power (as specified), 34 L calibration gas cylinder(s) with regulator(s).

Accessories

MMC USB Reader
Manual Aspirator Pump
MicroDock II—Automatic Calibration and Test Station

Vehicle Charger
Carrying Holster

GasAlertMicro 5 IR

CO₂, H₂S, CO, O₂, SO₂,
PH₃, NH₃, NO₂, HCN, Cl₂,
ClO₂, O₃, and Combustibles

Five-Gas Detector

GasAlertMicro 5 IR portable gas detector simultaneously monitors up to five atmospheric hazards including CO₂, oxygen, combustible gas (% LEL), and a wide selection of individual electrochemical toxic sensors. Compact and lightweight, **GasAlertMicro 5 IR** activates audible, visual and vibrating alarms in the event of a low, high, TWA or STEL alarm condition.

Highly configurable to suit a range of applications, **GasAlertMicro 5 IR** comes as a diffusion or pumped instrument; with either alkaline or NiMH rechargeable hot-swappable battery pack and has optional datalogging capabilities. Standard features include confidence beep, automatic calibration, full function self-test, and an extended selection of user-settable field options.

SPECIFICATIONS

DETECTOR: 1, 2, 3, 4, or 5-gas detector

Gas	Measuring Range	Default Resolution	High Resolution	TWA	STEL	LOW	HIGH
O ₂	0-30.0%	0.50%	N/A	N/A	N/A	19.5	23.5
H ₂ S	0-300 ppm	1.0 ppm	0.1 ppm	10	15	10	15
CO	0-999 ppm	1.0 ppm	N/A	35	50	35	200
TwinTox (H ₂ S)	0-300 ppm	1.0 ppm	0.1 ppm	10	15	10	15
TwinTox (CO)	0-500 ppm	1.0 ppm	N/A	35	50	35	200
PH ₃	0-5.0 ppm	1.0 ppm	0.1 ppm	0.3	1.0	0.3	1.0
SO ₂	0-100 ppm	1.0 ppm	0.1 ppm	2	5	2	5
NO ₂	0-99.9 ppm	1.0 ppm	0.1 ppm	2.0	5.0	2.0	5.0
HCN	0-30.0 ppm	1.0 ppm	0.1 ppm	4.7	10.0	4.7	10.0
Cl ₂	0-50.0 ppm	1.0 ppm	0.1 ppm	0.5	1.0	0.5	1.0
NH ₃	0-100 ppm	1.0 ppm	0.1 ppm	25	35	25	50
ClO ₂	0-1.00 ppm	0.1 ppm	0.01 ppm	0.1	0.3	0.1	0.3
O ₃	0-1.00 ppm	0.1 ppm	0.01 ppm	0.1	0.1	0.1	0.1
IR-CO ₂	0-50,000 ppm	25 ppm	N/A	5,000	30,000	5,000	30,000
LEL	0-100% LEL 0-5.0% v/v	1%	N/A	N/A	N/A	10%	20%

Auto zero: Yes

Calibration: Automatic

Backlight: Standard Mode: low light (auto); alarm condition (auto); reactivation on demand

Alarm Only Mode: alarm condition (auto); reactivation on demand

Stealth Mode: backlight inactive; audible and visual alarms silenced

Infrared CO₂; plug-in, electrochemical cell (toxic and oxygen); catalytic (LEL)

User field options: Confidence beep, set STEL period, force calibration on start-up, enable / disable sensor, pass code protection, latching alarms, span level, passed calibration user-lockout option, "SAFE" display function, stealth mode, fast pump, oxygen auto-cal on start-up, alarm only backlight mode, combustible gas measurement (% LEL or % by volume methane), LCD language option, STEL calculation choice, TWA calculation choice, combustible correction factor options, CO₂ zero/bypass during calibration, user-settable calibration gas level, high resolution, clock

Pump: Tubing length up to 100 ft. / 30 m (50 ft. / 15 m standard) with user options

ALARM INDICATORS: Clearly advises alarm conditions with audible, visual, and vibrator alarms

Visual alarms: Two flashing alarm bars visible from all angles

LCD indicates gas present and alarm levels encountered

Audible alarm: Typically 95 dB at 1 ft. / 30 cm variable pulsed audible alarm

Vibrator alarm: Pulses warning in gas alarm conditions, or for any status alarms

Status alarms: Low battery, over range, multiple gas / pump and failed or missing sensor

ALARM LEVELS: Instantaneous Low Alarm for all gases; Instantaneous High Alarm for all gases; TWA (time-weighted average) and STEL (short-term exposure limit) for toxics/CO₂

LCD: Continuous, alphanumeric gas readout and status display advises:

Gases monitored: CO₂, H₂S, CO, O₂, SO₂, PH₃, NO₂, NH₃, HCN, Cl₂, ClO₂, O₃ and/or combustibles (0-100% LEL or 0-5.0% methane)

Gas concentration: Simultaneously and continuously displays gas concentration(s) for all sensors (in ppm, % LEL, or % v/v)

Peak (max)/STEL/
TWA ppm or %: Records exposures and displays on demand

Alarm setpoints: Displayed on activation and on demand

Calibration due date: Days remaining on start-up

Clock: Real-time clock setting displayed on start-up or on demand

TESTS:

Full function self-test: Sensor integrity, circuitry, battery and audible/visual alarms on activation

Battery: Continuous

GENERAL SPECIFICATIONS: Rugged, composite material; two-shot molded polymer case with integral anti-shock boot

Operating temperature: -4 to 122°F / -20 to 50°C

Humidity: 0 - 95% RH (non-condensing)

EMI/RFI: Complies with EMC Directive 89/336/EEC

Protection: Highly water resistant and dust proof housing

Battery Options: Up to 10 hours operation without pump / up to 8 hours with pump for "hot-swappable" rechargeable and AA alkaline battery packs

Size: 5.7 x 2.9 x 1.5 in. / 14.5 x 7.4 x 3.8 cm

Weight: 13.1 oz. / 370 g

WARRANTY: Full 2-year warranty including all sensors (1 year CO₂ and NH₃ sensors)

DATALOGGER OPTIONS: User-downloadable datalogger



Data recorder: All events and occurrences (calibration zero adjustment, calibration span adjustment, gas readings, TWA, STEL, alarm condition, failures detected by the microprocessor).

Sampling rate: Factory set at 5-second intervals and user-settable from 1 to 127-second intervals

Storage: 2 months of continuous data at 5 second intervals via 32 MB Flash MMC card (64 MB and 128 MB cards also available); when full, the wrap-around feature replaces oldest data with most recent data

DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

RATINGS AND CERTIFICATIONS:  Class I, Div. 1, Gr. A, B, C, D
(Intrinsic safety)  American Bureau of Shipping

ATEX:  II 1 G T4
 EEx ia IIC T4
IECEx: Ex ia IIC T4

Locally distributed by: