



**For further information on the
BW Technologies range of products**

Contact Us

Toll Free: 1800 607 558

Telephone: +61 8 9244 4566

Facsimile: +61 8 9244 4577

Address: Unit 2/81 Guthrie Street, Osborne Park WA 6017

Email: info@accessunlimited.com.au

Web: www.accessunlimited.com.au

GasAlertMicro 5 PID

Five-Gas
Detector

VOCs (PID), H₂S, CO, O₂, SO₂, PH₃, NH₃, NO₂, HCN, Cl₂, ClO₂, O₃, and
Combustibles



Protect Yourself

- Smaller and over 50% lighter than competitive instruments
- Water-resistant design in an integral concussion-proof enclosure
- Continuous LCD shows simultaneous gas concentrations for five gases
- 0 - 1000 ppm measurement of VOCs (Volatile Organic Compounds)
- Integral motorized pump option for remote sampling
- Two power options: AA alkaline or rechargeable hot-swappable battery pack
- Provides 95 dB alarm tone and two bright wide-angled alarm bars
- Equipped with internal vibrating alarm for high noise areas
- Multi-language support in English, French, German, Spanish, and Portuguese
- Three backlight options: standard-activates in low light (auto), in alarm (auto) and reactivates on-demand; alarm only- activates in alarm conditions and reactivates on-demand; stealth mode
- Four alarm levels: instantaneous Low and High Alarm for all gases; TWA (time-weighted average) and STEL (short-term exposure limit) for VOCs and toxic gases
- Simple automatic calibration procedure; compatible with BW MicroDock II automatic test and calibration station
- Records TWA, STEL, and maximum exposures to gas and displays readings on command
- User selectable field options include: PID correction factor, language selection, confidence beep, span level, set TWA/STEL calculation choice, set calibration due date, pass code protection, latching alarm, 'SAFE' display function, stealth mode, and selectable ppm resolution for some gases (e.g. SO₂ 0.1 ppm)
- Full function self-test of: sensor, battery and circuit integrity; and audible/visual alarms